

EVERYTHING (surface)

Code: 806423182 (MM18.60)



Length: 1800mm
Section: 94x94mm
Weight: 7,4 kg net.



Features

Surface mounted or Pendant profile suitable installing under a solid ceiling

- Energy saving
- Full intensity from switch on
- Multiple (6 x) warm white 3.000°K LED nominal 7W
- Low operating temperature
- Long life
- Futureproof LED's and fully interchangeable
- Integral driver with S.E.L.V. output
- Non-Dimmable (Standard)
- Dimmable on demand

Suspension set 1,5m to order
Code: 806590000 (MMSS15)



Electrical Data

LED DRIVER (each)

Type	constant current
Input voltage	220/240Vac 50/60Hz
Input current	max. 0,16A
cos φ	>0,5

Electrical safety	Class II
Output isolation	S.E.L.V.

LUMINAIRE	
Electrical safety	Class III
Earthed housing	

LEDs	
Power per lighting unit	7 W @ 700 mA
Warm White	2875-3200K

Secondary connection	Top Connector prewired plug and socket to each lighting unit ready to install
----------------------	--

WARNING
Not for TRIAC-based (transistor, thyristor) switching.
Damage to driver inevitable

LED

IBL Gen⁴ LED lighting unit with CREE XLamp® MHD-E LEDs

Color Temperature CCT:	3000 K
Light Output:	approx. 650 lm per LED

CRI:	≥80
L70 Lifetime:	30 000 h



Contact

IBL Lighting GmbH
Christinenstr. 11
D-40880 Ratingen
Tel: 02102- 94 20 66 0
Fax: 02102- 94 20 66 6
web: www.ibl.eu
email: info@ibl.eu

ECO-Dashboard

